

# WorkCentre™ 7120 / 7125

## Colour Multifunction System



**WorkCentre 7120 / 7125V\_S**  
Two trays and stand configuration



**WorkCentre 7120 / 7125V\_T**  
Four tray configuration shown with Office Finisher, Booklet Maker and work surface options

		WorkCentre 7120	WorkCentre 7125
<b>Output Speed – Printing and Copying</b>			
<b>Black and white</b>		Up to 20 ppm (pages per minute) A4/210 x 297 mm LEF Up to 11 ppm A3/297 x 420 mm	Up to 25 ppm A4/210 x 297 mm LEF Up to 14 ppm A3/297 x 420 mm
<b>Colour</b>		Up to 20 ppm A4/210 x 297 mm Up to 11 ppm A3/297 x 420 mm	Up to 25 ppm A4/210 x 297 mm LEF Up to 14 ppm A3/297 x 420 mm
<b>First-Page-Out Time</b>			
<b>Copy – Black and white</b>		As fast as 6.5 seconds	
<b>Copy – Colour</b>		As fast as 8.1 seconds	
<b>Paper Handling</b>			
<b>Paper Handling – Duplex Automatic Document Feeder</b>			
<b>Capacity</b>		110 sheets (based on 75 gsm paper)	
<b>Speed</b>		55 images per minute Colour / Black and white (A4 long edge feed (LEF))	
<b>Sizes</b>		A5/148 x 210 mm to A3/297 x 420 mm SEF Custom sizes: 85 x 125 mm to 297 x 432 mm	
<b>Weights</b>		38 to 128 gsm	
<b>Paper Handling – Bypass Tray</b>			
<b>Capacity<sup>1</sup></b>		50 sheets	
<b>Sizes</b>		Custom sizes: 89 x 98 mm to 297 x 432 mm	
<b>Weights</b>		60 to 216 gsm	
<b>Types</b>		Same as front-loading trays plus envelopes, postcard, glossy media and labels	

<sup>1</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

Paper Handling – Trays 1 & 2 (with Stand) or Trays 1 - 4	
Capacity <sup>1</sup>	520 sheets each
Sizes	User adjustable from A5 to A3, Custom sizes: 140 x 182 mm to 297 x 432 mm
Weights	60 to 256 gsm
Types	Plain Paper Recycled Bond Custom Type 1 through 5 Heavyweight Extra Heavyweight Punched Letterhead Pre-printed
Total Capacity	2 Trays with Stand: 1,090 sheets 4 Trays: 2,130 sheets
Envelope Tray (Optional – replaces Tray 1)	
Capacity <sup>1</sup>	Up to 60 envelopes
Sizes	Monarch, DL, C5, Custom sizes: 98 x 148 mm to 162 x 241 mm
Weights	75 to 90 gsm
Output – Standard	
Stacking Trays <sup>1</sup>	Dual Catch Tray – up to 250 sheets each, lower tray offsets
Sizes	89 x 98 mm to A3/297 x 420 mm
Weights	60 to 256 gsm
Output – Integrated Office Finisher Option	
Stacking Tray	500 sheets of 75 gsm (A4) or 250 sheets of 75 gsm (A3)
Sizes	89 x 98 mm to A3/297 x 420 mm
Weights	60 to 220 gsm
Stapling	Single Auto stapling: 50 sheets maximum: A4/B5-size sheets (less than 90 gsm or two sheets of 220 gsm covers) 30 sheets maximum: A3/B4-size sheets (less than 90 gsm or two sheets of 220 gsm covers)
Output – Office Finisher LX Option	
Stacking Tray	2,000 sheets unstapled or 1,000 sheets single staple or 750 sheets dual staple (90 gsm A4)
Sizes	182 x 210 mm to A3
Weights	60 to 220 gsm
Stapling	Single and dual Auto stapling (50 sheets maximum less than 90 gsm) A3, A4, B4 and B5 sizes supported

<sup>1</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

Output – Optional Hole Punch for Office Finisher LX	
	2 & 4 Hole Punch (Driver Selectable)
Output – Optional Booklet Maker (Score/Crease, Saddle-stitch Staple) for Office Finisher LX	
<b>Capacity</b>	40 booklets (1-15 sheets per booklet – 80 gsm or less; 2-10 sheets per booklet – over 80 gsm)
<b>Sizes</b>	A4/210 x 297 mm 216 x 356 mm A3/297 x 420 mm
<b>Saddle-stitch Stapling</b>	2-15 sheets / 8 – 60 page booklet 55 to 90 gsm
<b>Score/Crease</b>	1-15 sheets / unstapled
Copy Specifications	
<b>Document Scanner</b>	Duplex Automatic Document Feeder with 110-sheet capacity (based on 75 gsm paper)
<b>Sides (input:output)</b>	1:1, 1:2, 2:2 and 2:1
<b>Quantity</b>	1 to 999
<b>Resolution</b>	600 x 600 dpi
<b>Concurrency</b>	Concurrent scan, print, fax
<b>Digital Imaging</b>	Auto colour Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Colour balance, colour shift and saturation
<b>Reduction/Enlargement</b>	Variable zoom from 25 % to 400 % in 1 % increments Anamorphic zoom Six user-programmable percentages

<b>Special Features</b>	<p>Auto paper select          Auto reduction/enlargement to fit selected paper size          Auto tray switching          Automatic job recovery          Auto colour selection          Area Designation          Poster mode          Watermark          Annotation          Booklet creation          Multi-up – 2, 4 or 8 up          Repeat Image          Negative image          Mirror image          Covers insertion (front only, front and back, back only, blank or printed)          Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder)          Job interrupt          Simple copy menu          Book copying          Sample job          Mixed-size originals          Hole Punch (requires Office Finisher LX)          Saddle-stitch booklets (requires Office Finisher LX)          Single position stapling (requires Integrated Office Finisher or Office Finisher LX)          Multi-position stapling (requires Office Finisher LX)          ID Card Copy</p>
<b>Foreign Device Interface</b>	<p>Interface to third-party access control devices, coin machines and card readers          Supports a variety of vending stations available through the Xerox Alliance Partner Programme</p>
<b>Print Specifications</b>	
<b>First-Page-Out Time</b>	
<b>Print – Black and white</b>	As fast as 11 seconds
<b>Print – Colour</b>	As fast as 13 seconds
<b>System</b>	
<b>Memory</b>	2 GB
<b>System Disk</b>	Minimum 80 GB
<b>Network Printing – Network Controller</b>	
<b>Processor</b>	667 MHz
<b>Printer Languages</b>	<p>Adobe® Postscript® 3™ (optional)          TIFF          PS-PDF: v1.6          PCL® 6          XPS®          HP-GL2 via direct submission</p>
<b>Network Printing – Resolution</b>	
	Print Engine: 600 x 600 x 4 dpi

Network Printing – Printing Features	
<b>Features</b>	Secure Print Delay Print (specific time) Sample Set Booklet creation Cover selection Inserts and exception pages Store File in Folder Paper selection by attribute N-up Saddle-stitch booklet making (requires Office Finisher LX) Hole Punch (requires Office Finisher LX) Watermark Fit to new paper size Banner Sheet enable/disable Output tray selection Image Quality Draft Mode Reduce/enlarge Mirror image Margins Bidirectional status Two sided printing Scaling LAN Fax (requires optional Fax Kit)
<b>Connectivity</b>	Ethernet 10/100BaseTX High speed USB 2.0 printer port Wireless Ethernet (IEEE 802.11b) via third-party adaptors
<b>Operating Systems</b>	Microsoft® Windows® XP SP3 and above (32- and 64-bit), Windows Server 2003 (32- and 64-bit), Windows Vista (32- and 64-bit), Windows Server 2008 (32- and 64-bit), Windows 7 (32- and 64-bit) Mac OS® 10.4 and above AIX 5 v5.3 HP UX 11.0, 11i v2 Solaris 8, 9, 10 Linux® FedoraCore 1, 5 RedHat Enterprise Linux 4 SUSE 10/11
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6 Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP and NetBEUI (All protocols not in use can be disabled)
<b>Administrative Protocols</b>	DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet, SSL
<b>Fonts</b>	Postscript 3: 136 Type 1 fonts, 2 Multiple Master fonts PCL: 82 scalable fonts, line printer bitmap font

Printer Drivers	Environment	PCL 6	PostScript
Print Drivers	Windows 2003/XP SP1 and above (32- and 64-bit) Windows Vista 32- and 64-bit Windows Server 2008 (32- and 64-bit) Windows 7 (32- and 64-bit) (Microsoft certified)	Bidirectional with user-selectable interface (standard <sup>2</sup> and enhanced <sup>3</sup> )	Bidirectional with user-selectable interface (standard <sup>2</sup> and enhanced <sup>3</sup> )
	Macintosh® OS 10.4	N/A	Generic PPD file
	Macintosh® OS 10.5 and above	N/A	Bidirectional with user selectable interface
	UNIX	N/A	Bidirectional with Xerox Custom Graphical User Interface
<b>Xerox Mobile Express Driver (X-MED)</b>	<p>Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of “favourite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.</p> <ul style="list-style-type: none"> <li>• Printers are automatically discovered</li> <li>• Printer list can be managed based on location</li> <li>• Gives Bidirectional feedback device status, supplies, queue management</li> </ul>		
<b>Xerox Global Print Driver (X-GPD)</b>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p> <ul style="list-style-type: none"> <li>• Printers are automatically discovered</li> <li>• Printer list can be managed based on location</li> <li>• Gives Bidirectional feedback device status, supplies, queue management</li> </ul>		
<b>Print Submission Tools</b>	<ul style="list-style-type: none"> <li>• Command prompt LPR/UNIX tool for print submission</li> <li>• Contents Bridge tool supports TIFF/PDF/XPS and Office 2007 direct print</li> </ul>		
<b>Device Management</b>			
<b>Management Support</b>	SNMP Version 1, SNMP Version 2c and Version 3 trap over TCP/IP and IP MIB access (IETF-MIB II RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v. 2		
<b>Xerox CentreWare® Web</b>	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>		
<b>IP Filter</b>	<p>Allows administrator to control print access to device via IP address. Restrict access to device to/from network</p>		
<b>Xerox CentreWare® for Unicenter TNG®</b>	<ul style="list-style-type: none"> <li>• Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View</li> <li>• Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk</li> </ul>		
<b>Xerox CentreWare® for Microsoft System Center Operations Manager (SCOM)</b>	<ul style="list-style-type: none"> <li>• Provides the identification of Xerox printers on the network and populates the SCOM database</li> <li>• Automatically changes the status and colour in the printer icon to reflect the printer status in each view. Events and alerts are also available in the Operator console</li> <li>• Easily access embedded web server through the icon displayed in the Xerox agent</li> <li>• Manage Xerox devices on network by displaying all discovered printers in a folder in any available Operator console view</li> <li>• Provides full use of Management Packs, Administrator and Operator console to ease management process</li> <li>• Using SNMP trap-capable Xerox devices enables unsolicited device feedback for device events (for example, machine out of toner)</li> </ul>		

<sup>2</sup> Standard: Driver based on Microsoft tree structure user interface (includes Xerox features and functionality)

<sup>3</sup> Enhanced: Xerox custom graphical user interface

<b>Xerox CentreWare® for Microsoft Management Console (MMC)</b>	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.
<b>Xerox CentreWare® for HP® OpenView®</b>	<ul style="list-style-type: none"> <li>• Provides for the identification of Xerox WorkCentre multifunction systems in the general discovery performed by HP OpenView</li> <li>• Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via colour-coded icons</li> <li>• Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView</li> </ul>
<b>Xerox Device Types for SAP R/3 Environment</b> <i>Information available at <a href="http://www.xeroxofficesap.com">www.xeroxofficesap.com</a></i>	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): <ul style="list-style-type: none"> <li>• Simplex or duplex printing</li> <li>• Finishing – single or dual stapling</li> <li>• Tray pull location from any tray</li> <li>• Print security via PIN ID capability at the WorkCentre</li> </ul>
<b>Xerox SAP R/3 Intelligent Barcode Utility (Optional)</b> <i>Information available at <a href="http://www.xeroxofficesap.com">www.xeroxofficesap.com</a></i>	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded on network controller <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> </ul>
<b>Xerox Barcode Pro PS</b> <i>Information available at <a href="http://www.xeroxofficesap.com">www.xeroxofficesap.com</a></i>	Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.
<b>Smart eSolutions</b>	
<b>MeterAssistant</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. Device Direct or via Smart eSolutions Client for Windows or via CentreWare Web.
<b>SuppliesAssistant</b>	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory. Device Direct or via Smart eSolutions Client for Windows or via CentreWare Web.
<b>CentreWare® Internet Services – Integrated Device Web Page</b>	
<b>Device Status</b>	Web server embedded on device controller <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> </ul>
<b>Print Queue Viewing</b>	Complete job print queue management – promote and delete
<b>Job Submission</b>	Print-ready files (PS, PCL, TIFF, PDF, XPS) Output feature selection
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Netscape Navigator® Mozilla Firefox® Microsoft® Internet Explorer Apple® Safari™

Fax Specifications	
Server Fax Enablement (Optional)	
<b>Fax Send Features</b>	<ul style="list-style-type: none"> <li>One-sided, two-sided, or two-sided rotate side 2</li> <li>Phone number entry</li> <li>Add to send list (50 numbers maximum)</li> <li>Delay send (specific time)</li> <li>Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi)</li> <li>Original type (photo, text, or photo and text)</li> </ul>
<b>Fax Print Features</b>	<ul style="list-style-type: none"> <li>One or two-sided printing</li> <li>Quantity</li> <li>Staple on/off</li> <li>Collate on/off</li> <li>Finisher output tray selection</li> <li>Secure print on/off</li> </ul>
<b>Fax Vendors</b>	<ul style="list-style-type: none"> <li>Multiple vendors, certified by the Xerox Alliance Partner Programme</li> <li>For details, visit <a href="http://www.xerox.com">www.xerox.com</a></li> </ul>
PSTN Fax (Optional) – One or Three Line Fax Option	
	<ul style="list-style-type: none"> <li>ITY (CCITT) group 3 quality/resolution superfine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi</li> </ul>
<b>Speed/Modem(s)</b>	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adaptor.
<b>Speed/Compression</b>	MH/G3, MMR/G4, JBig Super G3
<b>Fax Send Features</b>	<ul style="list-style-type: none"> <li>LAN Fax - Fax from print driver</li> <li>Auto fax transmission reduction</li> <li>Page-by-page job status at the machine</li> <li>Fax from platen</li> <li>Delay start</li> <li>Automatic memory resend</li> <li>Automatic cover sheets</li> <li>Priority send</li> <li>Broadcast</li> <li>Booklet Scan</li> <li>Up to 50 group dials with up to 20 recipients per group</li> </ul>
<b>Fax Receive Features</b>	<ul style="list-style-type: none"> <li>One or two-sided printing</li> <li>Reduction at reception to fit available paper</li> <li>Junk Fax prevention</li> <li>Thumbnail Preview</li> </ul>
<b>Fax Forward</b>	Faxes can be received into a folder on the device hard drive. Images that are in the folder can be routed to a combination of Email addresses, FTP or SMB sites or locations or Fax destinations.
<b>Fax Reports</b>	<ul style="list-style-type: none"> <li>Activity report</li> <li>Address Book</li> <li>Transmission confirmation</li> <li>Pending fax</li> <li>Folder List</li> </ul>
<b>Fax Receive Mailboxes</b>	Up to 200 password-protected folders
<b>Auto Dialing</b>	Auto redial, Batch send



Internet Fax (Optional) – Standard with One or Three Line Fax Option	
<b>Capability</b>	Direct document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents in black and white sent via email from remote Internet Fax machines or email clients
<b>Maximum Scan Area</b>	A3
<b>Address Directory Access</b>	Downloaded address list (comma-separated value file format)
<b>File Formats</b>	TIFF-FX Profiles S with G3 MH, F with G4 MMR, or J with JBIG
<b>Resolutions</b>	600 x 600 dpi 400 x 400 dpi 200 x 200 dpi 200 x 100 dpi Bit Depth: 1 bit (monochrome)
<b>Network Protocols</b>	SMTP POP3
<b>Compliance</b>	ITU-T T.37 compliant
Fax over IP (Optional)	
	T.38 compliant IP fax/resolution superfine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi
<b>Fax Send Features</b>	LAN Fax - Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast Booklet Scan
<b>Fax Receive Features</b>	One or two-sided printing Reduction at reception to fit available paper Junk Fax prevention Thumbnail Preview
<b>Fax Forward</b>	Faxes can be received into a folder on the device hard drive. Images that are in the folder can be routed to a combination of Email addresses, FTP or SMB sites or locations or Fax destinations.
<b>Fax Reports</b>	Activity report Address Book Transmission confirmation Pending fax Folder List
<b>Fax Receive Mailboxes</b>	Up to 200 password-protected folders
<b>Auto Dialing</b>	Auto redial, Batch send
Scan Specifications	
Scan to Email (Standard)	
<b>Capability</b>	Colour scanning, Auto Colour, Grey scale, Black and White Direct document email from device Manual or directory Exchange/Notes/LDAP address searching Signing and encryption Email over SSL Preview scan job
<b>Network Protocol</b>	SMTP, S/MIME, POP3

<b>File Formats</b>	TIFF 6.0 or TTN2 with JPEG, G3MH, G4 MMR compression (single page or multiple pages) PDF, PDF/A with MRC, JPEG, G4 MH, G4 MMR, MRC, JBIG 2 Huffman, JBIG Arithmetic Compression JPEG XPS Searchable PDF, PDF/A, XPS Password Protected PDF Encrypted PDF Linearised PDF
<b>Authentication</b>	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication)
<b>Directory Access</b>	Corporate address list via LDAP Downloaded address list (comma-separated file format)
<b>Scan to Folder</b>	
<b>Capability</b>	Colour, Auto Colour, Black and White
<b>Features</b>	Images can be scanned, printed and faxed directly to the device hard drive and stored in a folder. Scan or fax images that are stored in the folder can then be printed, emailed, sent via fax, sent via IFax, routed to a PC, an FTP or SMB site via Job Flow Sheets. Thumbnail Preview
<b>Network Scanning (Optional)</b>	
<b>Capability</b>	Colour Scanning, Grey scale, Black and White, Auto Colour
<b>Concurrency</b>	Scan while printing or while it is transferring scan to network or fax jobs
<b>Input Speed</b>	Scan at 55 ipm Colour / Black and white (216 x 279 mm/A4 long edge feed)
<b>Resolution</b>	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
<b>Maximum Scan Area</b>	297 x 432 mm
<b>Network Protocol</b>	FTP via TCP/IP Microsoft SMB via TCP/IP Netware, HTTP and HTTPS
<b>File Formats</b>	TIFF 6.0 or TTN2 with JPEG, G3MH, G4 MMR compression (single page or multiple pages) PDF, PDF/A with MRC, JPEG, G3 MH, G4 MMR, MRC, JBIG 2 Huffman, JBIG Arithmetic Compression JPEG XPS Searchable PDF, PDF/A, XPS Password Protected PDF Encrypted PDF Linearised PDF
<b>Document Management Fields</b>	One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard
<b>Scan Features</b>	Mixed size originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality/File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job

<b>Supported Scan Destinations (Varies by scanning software options purchased.)</b>	<p>Scan to network server          Scan to remote email destinations via direct SMTP addresses or via various network scanning software options          Scan to application (Electronic Document Management System/Repositories)          Scan to Microsoft Exchange 2000 Web Folders          Scan to PC Desktop® (Professional and SE editions)          SMARTsend®          ScanFlowStore®          Scan to Windows XP client SMB or FTP          Scan to Folder          Scan to Home          Scan to USB</p>
<b>Scan to PC Desktop SE (Optional)</b>	<ul style="list-style-type: none"> <li>• A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools</li> <li>• Nuance PaperPort – image viewing and file management software</li> <li>• Nuance OmniPage (for desktop/client installation) – OCR and file format conversion software</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops.</li> </ul>
<b>Scan to PC Desktop Pro (Optional)</b>	<ul style="list-style-type: none"> <li>• A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools</li> <li>• The PaperPort Personal Scanning Platform empowers office workers with the ability to customise, directly from the desktop, the scanning menus available to them on Xerox EIP enabled multifunction systems.</li> <li>• Nuance PaperPort Pro – image viewing and file management software</li> <li>• Nuance OmniPage Pro (for desktop/client installation) – OCR and file format conversion software</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox or through email WorkCentre to individual desktops. Also includes an Email inbox polling capability.</li> </ul>
<b>Thumbnail Preview (Standard)</b>	
Images that are stored in the folder on the device hard drive can be viewed at the User Interface.	
<b>Device Specifications</b>	
<b>Security</b>	
<b>Capability</b>	<p>Secure Print, NDS Authentication over IP, LDAP/Kerberos/SMB, Password Protected PDF and Encrypted Scan to Email.          Secure Web Page via SSL.          FIPS 140-2          IP Sec          Audit Log          SSL/TLS          IP filtering          802.1X          SMIME          Watermark          Annotation          PDF/XPS signatures          Digital certificate management          Email over SSL          Image Overwrite          Encrypted Disk</p>
<b>Secure Access and Authentication</b>	<p>Optional secure device login with network user name and password          Remote Authentication: Kerberos (Windows Server 2003, Windows Server 2008, Windows 7, UNIX), SMB (Windows Server 2003, Windows Server 2008, Windows Vista, Windows 7)          Local authentication          LDAP</p>
<b>Accounting</b>	
<b>Auditron (Local Accounting)</b>	Controls and tracks black and colour copy, print, fax and scan usage
<b>Accounting with Third-Party Server Applications (optional)</b>	Up-to-the-minute data on how the system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax

<b>Accounting Control</b>	Xerox Standard Accounting Job based accounting Third-party integration through Network Accounting Enablement Kit Supports Foreign Device Interface Active directory user profile – Controls colour copy and print usage and feature/pathway control Xerox Page Accountant Print Audit 5	
<b>Accounting – Xerox Standard Accounting</b>		
<b>Tracking</b>	Copy, Print, Fax and Scan usage	
<b>Accounting</b>	Up to 2,500 User accounts (User ID); Up to 500 Group accounts (Department)	
<b>Features</b>	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.	
<b>Monthly Duty Cycle</b>		
	WorkCentre 7120: Up to 50,000 pages/month WorkCentre 7125: Up to 60,000 pages/month	
<b>Basic Configurations</b>		
	Network Multifunction System with network controller – Copy, Print and Network Scan capability standard WorkCentre 7120 / 7125V_S: 2 Tray with Stand Configuration WorkCentre 7120 / 7125V_T: 4 Tray Configuration	
<b>Accessories</b>		
	One-line PSTN fax with Internet Fax Three-line PSTN fax with Internet Fax Fax over IP (T.38) Server Fax Enablement Scan to PC Desktop (Professional or SE edition) Media Print (Print from a media card) Scan to / Print from USB Integrated Office Finisher Office Finisher LX Booklet Maker (requires Office Finisher LX) Foreign Device Interface Convenience Stapler	
<b>Electrical Requirements</b>		
	220–240 V Nominal, 50/60 Hz, 10A	
<b>Power Consumption</b>	<b>WorkCentre 7120</b>	<b>WorkCentre 7125</b>
<b>Running (Avg)</b>	578 watts	578 watts
<b>Standby</b>	119 watts	119 watts
<b>Low-Power Mode</b>	74 watts	78 watts
<b>Sleep Mode</b>	3.08 watts	3.2 watts
<b>Warm Up</b>	40 seconds (maximum)	
<b>Low-Power Recovery</b>	29 seconds (maximum)	
<b>Required Temperature Range</b>	10° to 32° C	

## WorkCentre 7120 / 7125

<b>Required Relative Humidity</b>	15% to 85%			
<b>Noise Emission</b>	<b>WorkCentre 7120</b> 16 dB(A) standby 52 dB(A) running		<b>WorkCentre 7125</b> 16 dB(A) standby 53 dB(A) running	
<b>Heat Emission</b>	1734 BTU/Hr running 357 BTU/Hr standby		1957 BTU/Hr running 389 BTU/Hr standby	
<b>Dimensions and Weights</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
<b>Base Unit</b>	585 mm	640 mm	1132 mm	114 kg
<b>Xerox Extensible Interface Platform® (EIP)</b>				
	Xerox EIP is a software platform inside the WorkCentre 7120 / 7125 that enables personalised solutions you can access right from the device touch screen. These applications can leverage your existing databases and meet your specific business challenges.			
<b>Certifications</b>				
	FCC Class B Compliant (U.S./Canada) ENERGY STAR 89/336/EEC (Europe) TUV Listed CB Certified (IEC 60950-1/EN 60950-1) 73/23/EEC (Europe) Windows Hardware Quality Labs Blue Angel (Europe) EcoLogo Certified Common Criteria (ISO 15408) (pending)			
<b>Supplies</b>	<b>Description</b>	<b>Order Number</b>		
<b>Toner Cartridges</b>	Black Toner Cartridge - Metered	006R01453		
	Yellow Toner Cartridge - Metered	006R01454		
	Magenta Toner Cartridge - Metered	006R01455		
	Cyan Toner Cartridge - Metered	006R01456		
<b>Staple Refills</b>	Integrated Office Finisher	008R12941		
	Office Finisher LX	008R12941		
<b>Staple Cartridges</b>	Integrated Office Finisher	008R12964		
	Office Finisher LX	008R12964		
	Booklet Maker for Office Finisher LX	008R12897		

# WorkCentre 7120 / 7125

Smart Kits	Description	Order Number
	SMart Kit® Drum Cartridge Black Yellow Magenta Cyan	013R00657 013R00658 013R00659 013R00660
	SMart Kit® Fuser Module (220 V)	008R13088
	Waste Toner Container	008R13089
	Second Bias Transfer Roll	008R13086
	Transfer Belt	001R00610

